

0512 PUFAS EURO 3000 Vinyl Special Indicator

Resin-reinforced adhesive with pleasant lemon aroma and pink control
To make an evenly applying to the wallpaper easier.

Instructions for use: *EURO 3000 Vinyl Special Indicator* is ideally suitable for pasting light and heavy woodchip wallpapers, paper wallpapers and vinyl wallpapers on mineral surfaces and gypsum boards

Technical specifications:

Components:	Starch ether, poly vinyl acetate powder
Density:	approx. 0.3-0.4g/cm ³
pH-value:	approx. 8-9
Solubility:	Ready for use after approx. 5 minutes
Usage:	approx. 200 ml/m ²

Surface preparation: The surface must be dry, firm, and dust and grease-free. Remove old, peeling wallpapers and distempers using *PUFAS Wallpaper Remover*. Make good cracks and holes using *PUFAS Interior* or *PUFAMUR Super Bonding Filler*. Pretreat highly absorbent, sanding and chalking surfaces using *PUFAS Deeply Penetrating Primer – Solvent Free*.

Application: Stirring vigorously, sprinkle *PUFAS EURO 3000 Vinyl Special Indicator* into clean, cold water and continue to stir for some minutes. Leave for approx. 5 minutes and then stir vigorously again. The prepared adhesive with a pleasant lemon aroma is pink coloured to the make an evenly applying to the wallpaper easier.

Paste wallpaper evenly with *PUFAS EURO 3000 Vinyl Special Indicator* and fold over. After sufficient softening, apply on impact and press on.

After dryness the adhesive is transparent.

Always observe the wallpaper manufacturer's instructions for use.

Remove adhesive residues using a damp cloth.

Do not use if the object and room temperature are below + 5° Celsius!

Clean tools in water after use.

Mixing ratio:

for	Mixing ratio	Quantity of water per 300-g packet	Coverage of a 300-g packet
Pre-pasting	1:50	15 l	100-130 m ²
Light wallpaper	1:30	9 l	45-55 m ²
heavy wallpaper vinyl wallpaper	1:20	6 l	30-40 m ²

Storage: Store in a cool and dry place!

Article no.: 0512

Available size: 300 g collapsible box

Shelf life: Min. 5 years as of production date.
Date of manufacture – see print