

13 PUFAS Wallpaper Protector PUFAS Tapeten- und Anstrichschutz

Dirt and water repellent protective coating.

Instructions for use: PUFAS Wallpaper Protector is a colourless transparent, brushable, gloss coat-

ing for wallpapers, dispersion-based paints, plaster and similar substrates. For interior use. *PUFAS Wallpaper Protector* is not suitable for use on plastic, wood

or metal.

Technical information: Components: Acrylate dispersion

Density: 1.0 g/cm³ pH value: 7-8

Coverage per m²: 100-150 ml/m² per coating

Surface Preparation:: The surface must be dry, stable and free of dust, grease etc.

Application: PUFAS Wallpaper Protector is ready for use and can be applied using a brush

or a suitable spray application system. The glossiness of the coating depends on the surface structure of the substrate. For rough substrates, two coats are required to achieve an even, gloss coating. For silk lustre surfaces, *PUFAS*

Wallpaper Protector can be diluted 1:1 with water.

PUFAS Wallpaper Protector can be used as a rendering base, diluted up to 1:4

with water depending on the absorbency of the substrate.

Do not use if the temperature of the room or substrate is below 5°C.

Clean tools with water immediately after use.

Important information: Directive(2004/42/CE)Classification:

- CE VOC limit value for this product (cat. A/a, Wb): 100 g/l (2010)

This product contains max 1 g/I VOC

Storage: Store in a cool place, protect from frost! Ensure that the container is properly

closed during storage!

Article no.: 13

Available sizes: 250 ml PE bottle

1 I PE bottle 5 I PE bottle